

Claims

1. Method for automating the design of a ducting system for a fluid comprising the steps of
 5 entering boundary data (15, 17, 19, 20) identifying boundary conditions of the ducting system, into a data processing system, which boundary data comprises
 positional information (17) in a three dimensional installation space and magnitude of partial fluid flow (19, 20) for each of at least one component terminal connection, through which fluid is exchanged with the ducting system, wherein the fluid flow
 10 through said at least one component terminal connection has a common orientation, and positional information (15) in the three dimensional installation space of at least one main terminal connection, through which the total fluid flowing through the at least one component terminal connection is routed,
 determining design data (27, 43) by applying an optimization algorithm to said
 15 boundary data using said data processing system, which design data comprises
 an optimum layout (27) of said ducting system in the three dimensional installation space including an identification of all required ducting components (43) for building the ducting system, selected from a collection of standard ductwork primitives (51), and having said data processing system communicate the design data (27, 43) to an
 20 external recipient.
2. Method for automating the design of a ducting system according to claim 1, wherein
 said boundary data contains a uniform fluid velocity value (13) corresponding to a
 uniform desired flow speed of the fluid in all parts of the ducting system.
3. Method for automating the design of a ducting system according to claim 1 or 2, wherein
 said boundary data contains information determining said common orientation of the
 fluid flow through said at least one component terminal connection.
4. Method for automating the design of a ducting system according to any of claims 1 to 3,
 30 wherein a required throughput capacity of at least one pipe element (41), which is contained in said required ducting components (43), is calculated by the data processing means considering the position of the pipe element (41) within said optimum layout (27) of the ducting system and the magnitude of said partial fluid flow (19, 20) for

each of the at least one component terminal connection, while a uniform desired flow speed of the fluid in all parts of the ducting system is assumed.

- 5 5. Method for automating the design of a ducting system according to any of claims 1 to 4, wherein said boundary data (15, 17, 19, 20) contains information identifying a z-dimension (12), corresponding to the height of a trunk plane above the floor level of the three dimensional installation space, which floor level is defined by the x- and y- axes of the coordinate system and in which trunk plane a trunk pipe system (26) is configured, which provides connections to one main terminal location (15) and at least one drop
 - 10 (17), which is the location defined by the projection of the at least one component terminal connection along the z-axis into the trunk plane.
- 15 6. Method for automating the design of a ducting system according to claim 5, wherein said optimum layout (27) of said ducting system is determined by optimizing the configuration of said trunk pipe system (26), which contains at least one straight trunk pipe (28), wherein the orientations allowed for said at least one straight trunk pipe (28) are restricted to the directions of the x- and the y- axis of the coordinate system.
- 20 7. Method for automating the design of a ducting system according to claim 5 or 6, wherein said optimization algorithm to determine said optimum layout (27) of said trunk pipe system (26) comprises the steps of
 - dividing said drops (17) into two drop groups (29, 30) according to the location of drops (17) relative to said main terminal location (15) in x-direction,
 - 25 dividing each drop group (29, 30) into two side groups (31, 32) according to the location of drops (17) within said drop groups (29, 30) relative to said main terminal location (15) in y-direction,
 - applying a subdividing routine for subdividing input groups into at least one output group to each side group (31, 32), while the output group is named level 1 group
 - 30 (33), by assigning each drop (17) separated from any other drop (17) within the same input group by a distance of equal or less than a predetermined parameter to individual output groups,

3

10

15

20

- 30

including visualizations of said at least one component terminal connection, of said at least one main terminal connection, of at least one elbow device (40) if required by the layout, each of which is interfacing a pair of pipe elements (41) of different orientations, which pipe elements (43) are contained in said required ducting components (45), and
 5 of at least one branching device (39) if required by the layout, each of which is connecting at least 3 pipe elements (41).

10. Method for automating the design of a ducting system according to claim 9, wherein said step of having the data processing system communicate the design data (27, 43) to
 10 an external recipient results in a visual display of a list (43) of said required ducting components including their prices (50), which list is based on said visual display of the optimum layout (27).

11. Method for automating the design of a ducting system according to any of claims 1 to
 15 10, wherein said method can be utilized via the Internet through the use of web browsing software.

12. Means for automating the design of a ducting system for a fluid comprising
 data entry means, used to identify
 20 positional information (17) in a three dimensional installation space and magnitude of partial fluid flow (19, 20) for each of at least one component terminal connection, through which fluid is exchanged with the ducting system, wherein the fluid flow through said at least one component terminal connection has a common orientation, and positional information (15) in the three dimensional installation space of at least
 25 one main terminal connection, through which the total fluid flowing through the at least one component terminal connection is routed,
 a standard ductwork data base (51) containing a collection of standard ductwork primitives,
 data processing means applying optimization criteria in order to determine design data
 30 (27, 43), comprising
 an optimum layout (27) of said ducting system in the three dimensional installation space including an identification of all required ducting components (43) for building the ducting system, selected from said standard ductwork data base (51),

002734968-124200

and data output means, communicating said design data (27, 43) to an external recipient.

13. Means for automating the design of a ducting system according to claim 12, wherein
 5 said data entry means are used to identify a uniform fluid velocity value (13) corresponding to a uniform desired flow speed of the fluid in all parts of the ducting system.
14. Means for automating the design of a ducting system according to claim 12 or 13,
 10 wherein said data entry means are used to identify said common orientation of the fluid flow through said at least one component terminal connection.
15. Means for automating the design of a ducting system according to any of claims 12 to
 15 14, wherein a required throughput capacity of at least one pipe element (41), which is contained in said required ducting components (43), is calculated by the data processing means considering the position of the pipe element (41) within said optimum layout (27) of the ducting system, the magnitude of said partial fluid flow (19, 20) for each of the at least one component terminal connection, while a uniform desired flow speed of the fluid in all parts of the ducting system is assumed.
- 20 16. Means for automating the design of a ducting system according to any of claims 12 to 15, wherein said data entry means are used to identify a z-dimension (12), corresponding to the height of a trunk plane above the floor level of the three dimensional installation space, which floor level is defined by the x- and y- axes of the coordinate system and in which trunk plane a trunk pipe system (26) is configured,
 25 which provides connections to one main terminal location (15) and at least one drop (17), which is the location defined by the projection of the at least one component terminal connection along the z-axis into the trunk plane.
- 30 17. Means for automating the design of a ducting system according to claim 16, wherein said data processing means determine said optimum layout (27) of said ducting system by optimizing the configuration of said trunk pipe system (26), which contains at least one straight trunk pipe (28), wherein the orientations allowed for said at least one

0024968-1200

18. Means for automating the design of a ducting system according to claim 16 or 17,
5 wherein said optimization criteria used to determine said optimum layout (27) said trunk
pipe system (26) are based on an algorithm

dividing said drops (17) into two drop groups (29, 30) according to the location of drops (17) relative to said main terminal location (15) in x-direction,

15 applying a subdividing routine for subdividing input groups into at least one output group to each side group (31, 32), while the output group is named level 1 group (33), by assigning each drop (17) separated from any other drop (17) within the same input group by a distance of equal or less than a predetermined parameter to individual output groups.

20 iteratively applying said subdividing routine to said at least one output group of the
respective prior routine, as long as a pair of drops (17) separated by a distance of
equal or less than a respective parameter value, which is supplied from a list of
predetermined parameters of decreasing value, exists.

זי זאל זיך אריין שטעלן

5

5

10

15

25

30